

**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C07C 17/20, 19/10, 19/08</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/52844</b> <b>(43) International Publication Date:</b> 21 October 1999 (21.10.99)
<b>(21) International Application Number:</b> PCT/US99/06868 <b>(22) International Filing Date:</b> 30 March 1999 (30.03.99)  <b>(30) Priority Data:</b> 09/058,071                      9 April 1998 (09.04.98)                      US  <b>(71) Applicant:</b> ALLIEDSIGNAL, INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).  <b>(72) Inventors:</b> VAN DER PUY, Michael; 3 Exeter Road, Amherst, NY 14221 (US). EIBECK, Richard, Elmer; Apartment 18, 3340 W. Highway 89, Sedona, AZ 86336 (US). MADHAVAN, G., V., Bindu; 115 Himalaya Drive, Monroeville, PA 15146 (US). HSUEH, Sung, Tung; 16 Vassar Drive, Getzville, NY 14068 (US). ELLIS, Lois, Anne, Short; 35 James Road, Orchard Park, NY 14127 (US).  <b>(74) Agents:</b> CRISS, Roger, H. et al.; AlliedSignal Inc., Law Dept. (Amy Olinger), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).		<b>(81) Designated States:</b> JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> PROCESS FOR THE PREPARATION OF 1-CHLORO-1,1,3,3,3-PENTAFLUOROPROPANE  <b>(57) Abstract</b>  The invention relates to the preparation of 1-chloro-1,1,3,3,3-pentafluoropropane (HCFC-235fa), useful as an intermediate in the production of 1,1,1,3,3-pentafluoropropane (HFC-245fa). The invention further relates to a process for the preparation of HFC-245fa comprising reacting HCFC-235fa with hydrogen in the presence of a reduction catalyst wherein the said HCFC-235fa is prepared by reacting CCl <sub>3</sub> CHCl <sub>3</sub> with hydrogen fluoride in the presence of fluorination catalyst in either the liquid phase or the vapor phase.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**PROCESS FOR THE PREPARATION OF 1-CHLORO-1,1,3,3,3-PENTAFLUOROPROPANE****FIELD OF THE INVENTION**

This invention is related to the preparation of fluorine containing hydrohalocarbons. Specifically, it relates to the manufacture of 1-chloro-1,1,3,3,3-pentafluoropropane (referred to in the art as HCFC-235fa) in the presence of a fluorination catalyst either in the liquid phase or vapor phase. HCFC-235fa is useful as an intermediate in the production of 1,1,1,3,3-pentafluoropropane (referred to in the art as HFC-245fa).

The invention also relates to a process for the preparation of 1,1,1,3,3-pentafluoropropane comprising the step of producing 1-chloro-1,1,3,3,3-pentafluoropropane by reaction of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with hydrogen fluoride in the presence of a fluorination catalyst either in the liquid phase or the vapor phase.

**BACKGROUND OF INVENTION**

Fluorine containing hydrohalocarbons are of current interest due to their potential to replace ozone depleting chlorofluorocarbons, which are used in a variety of applications including refrigerants, propellants, blowing agents, and solvents. Both HCFC-235fa and HFC-245fa are known to be useful as blowing agents. HFC-245fa has physical properties, including a boiling point of about  $14^\circ\text{C}$ , that makes it particularly attractive as a blowing agent, refrigerant or propellant. Its ability to function in a manner similar to CFC-11 ( $\text{CCl}_3\text{F}$ , b.p.  $24^\circ\text{C}$ ), a well known aerosol propellant at the time, was noted by Smith and Woolf in U.S. Patent No. 2,942,036 (1960). European Patent Application EP 381 986 also states (using a generic formula) that  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  may be used as a propellant or blowing agent. The use of HFC-245fa as a heat transfer agent is also mentioned in JP 02/272,086 (Chem. Abstr. 1991, 114, 125031q).

Previously,  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  has been prepared by a liquid phase reaction of 1,1,1,3,3,3-hexachloropropane with HF in the presence of a catalyst, as disclosed in EP 0 522 639.

Commonly assigned U.S. Patent No. 5,728,904 discloses the preparation  
5  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  by fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with HF in the presence of either  $\text{TiCl}_4$  or  $\text{SnCl}_4$  catalysts, followed by reduction to HFC-245fa.

The preparation of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  by the  $\text{BF}_3$ -catalyzed addition of HF to  $\text{CF}_3\text{CH}=\text{CFCl}$  is also known (R.C. Arnold, U.S. Patent 2,560,838; 1951). The source of  $\text{CF}_3\text{CH}=\text{CFCl}$  was not disclosed.

10 HFC-245fa was first made by the reduction of  $\text{CF}_3\text{CCl}_2\text{CF}_2\text{Cl}$  over a palladium catalyst (Smith and Woolf, U.S. Patent 2,942,036, 1960). Materials exiting the reaction zone include  $\text{CF}_3\text{CH}_2\text{CHF}_2$ ,  $\text{CF}_3\text{CH}=\text{CF}_2$ ,  $\text{CF}_3\text{CCl}=\text{CF}_2$ , and unreacted starting material. The desired  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  was formed in yields up to about 60%, but the source of the starting material was not disclosed.

15 Reduction of 1,1,1,3,3-pentafluoropropene was disclosed by Knunyants et al. (Chem. Abstr., 1961, 55, 349f). The yield of pentafluoropropane was 70%.

Burdon et al., J. Chem. Soc., C, 1969, 1739 disclose the formation of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ , in low yield, during the elemental fluorination of tetrahydrofuran.

Commonly assigned U.S. Patent No. 5,574,192 discloses the fluorination of  
20  $\text{CCl}_3\text{CH}_2\text{CHCl}_2$  with HF/ $\text{SbCl}_5$  to produce HFC-245fa.

It is an object of this invention to provide a means of preparing 1-chloro-1,1,3,3,3-pentafluoropropane that is economical and amenable to large scale, using readily available raw materials.

It is a further object of this invention to provide a means of manufacturing 1,1,1,3,3-pentafluoropropane comprising reacting  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  with hydrogen in the presence of a reduction catalyst wherein the said  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  is prepared by reacting  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with hydrogen fluoride in the presence of a fluorination catalyst in either the liquid phase or the vapor phase.

It is a further object of this invention to provide a means of manufacturing 1,1,1,3,3-pentafluoropropane comprising the following steps:

- 1) the formation of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  by the reaction of  $\text{CCl}_4$  with vinylidene chloride;
- 2) the conversion of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  to  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  by reaction with hydrogen fluoride (HF) in the presence of a fluorination catalyst either in the liquid phase or in the vapor phase; and
- 3) reduction of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  to  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

Each step is conducted under process conditions, i.e., temperature and pressure, sufficient to produce the desired product as discussed herein.

## DETAILED DESCRIPTION

The telomerization of vinylidene chloride by reaction with  $\text{CCl}_4$ , is known in the art and has been studied in some detail. The telomerization reaction produces compounds of the formula  $\text{CCl}_3(\text{CH}_2\text{Cl})_n\text{Cl}$ , where  $n$  varies as needed for the products desired. The telomerization of vinylidene chloride can be initiated by several means, but initiation with metal salts, particularly of copper, has distinct advantages for the process of this invention. The copper salts are believed to initiate the reaction by first reacting with  $\text{CCl}_4$ , to produce a trichloromethyl radical which then combined with vinylidene chloride, initiating the telomerization (see for example, Assher and Vofsi, J. Chem. Soc., 1961, 2261 for a discussion of the mechanism). The copper salts also terminate the telomerization by chlorine atom transfer to the growing radical chain. Thus, the chain lengths are shortened

considerably, compared to e.g., peroxide initiated telomerizations. For the reactions of interest here, telomers having 3 to 9 carbon atoms are obtained in excellent yield. Some control of the telomer distribution is feasible by controlling the reaction conditions, notably the ratio of  $\text{CCl}_4$  to vinylidene chloride and the type of copper salt used (see for  
5 example Belbachir et al., Makromol. Chem. 1984, 185, 1583-1595). Thus, it is possible to obtain  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with very little higher molecular weight telomers (see Example 1).

A variety of catalysts have been used in telomerization processes. To a large degree, many of these telomerization catalysts, including mixtures thereof, can be equivalent, and the choice of catalyst depends on cost, availability, and solubility in the  
10 reaction medium. For the telomerization reaction of this invention, it was discovered that salts of copper and iron are preferred. Overall, for the reaction of interest here, the more preferred catalysts are cuprous chloride, cupric chloride, or mixtures of the two or cuprous iodide. The amount of catalysts used in the telomerization reaction is at least about 0.1 mmol, and preferably, about 0.1 to about 50 mmol, per mole of saturated  
15 halogenated hydrocarbon (e.g.,  $\text{CCl}_4$  or  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ ) used. At very low concentrations, the reaction rate may be unacceptably slow, and very high catalyst concentrations may be wasteful due to the fact that the solubility limit may have been reached at even lower catalyst to  $\text{CCl}_4$ , ratios. Consequently, the more preferred amount of catalyst is about 1 to 20 mmol, per mole of saturated halogenated hydrocarbon.

20 It is also noted that a co-catalyst can be used in the telomerization process. Amines may be employed as co-catalysts, preferably in concentration of 1 to 10 moles per mole of metal catalyst (i.e. copper salt). Such amine co-catalysts include alkanol amines, alkyl amines and aromatic amines, for example ethanolamine, butyl amine, propyl amine, benzylamine, pyridine and the like.

25 The ratio of  $\text{CCl}_4$  to vinylidene reactant will substantially alter the degree of polymerization, i.e. average value of  $n$  for compounds of the formula  $\text{CCl}_3(\text{CH}_2\text{CCl})_n\text{Cl}$ . Thus, for example, if the desired product has only one more  $-\text{CH}_2\text{CCl}_2-$  unit than the

starting material, the ratio of  $\text{CCl}_4$  (or  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ ) to vinylidene chloride should be relatively high (at least about 2, and preferably, about 2 to 5), so that higher molecular weight telomers are minimized. If the desired product has two or more  $-\text{CH}_2\text{CCl}_2-$  units than the starting material (e.g.,  $\text{CCl}_3(\text{CH}_2\text{CCl}_2)_2\text{Cl}$  from  $\text{CCl}_4$ ), smaller ratios of  $\text{CCl}_4$  to vinylidene chloride (about 0.3 to 1) should be used. The same rationale is used for a system employing vinylidene fluoride.

Useful temperatures for the telomerization reaction range from about  $25^\circ\text{C}$  to about  $225^\circ\text{C}$ , preferably about  $80^\circ\text{C}$  to about  $170^\circ\text{C}$ , so that, depending on reactant concentrations and catalyst activity, convenient reaction times will vary from a few hours to about one day. More preferred temperatures are in the about  $125^\circ\text{C}$  to about  $140^\circ\text{C}$  range.

Finally, a variety of solvents can be used. Any solvent which is inert to the reactants and the desired product can be used. Illustrative of such are acetonitrile, dimethylsulfoxide, dimethylformamide, tetrahydrofuran isopropanol, and tertiary butanol. We prefer acetonitrile due to its low cost, stability, easy recovery via distillation, and ability to dissolve sufficient amounts of inorganic catalyst salts. Primarily for the latter consideration, the amount of solvent is preferably from about one fourth to two thirds of the total volume, and more preferably one third to one half of the total volume. Otherwise, the amount of dissolved catalyst may be relatively low, or the output of product per run will be adversely affected due to a dilution effect.

In the second step,  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  is fluorinated to provide  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ . We have found that pentavalent antimony halides catalysts may be used to fluorinate  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  to provide  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ , but a critically narrow set of operating conditions, particularly with respect to temperature, mole ratio of HF to organic and catalyst concentration, must be employed to avoid over-fluorination. At high catalyst concentrations and/or high reaction temperatures the rate of the fluorination step is rapid,

but selectivity declines to an unacceptable level. The higher the temperature, the more over-fluorinated product,  $\text{CF}_3\text{CH}_2\text{CF}_3$  (referred to in the art as HFC-236fa), is produced.

Due to the temperature required, about  $50^\circ\text{C}$  to about  $100^\circ\text{C}$ , preferably from about  $60^\circ\text{C}$  to about  $95^\circ\text{C}$ , most preferably about  $65^\circ\text{C}$  to about  $90^\circ\text{C}$ , the reactions are  
5 conducted under pressure. The pressure may be controlled by release of by-product  $\text{HCl}$ , during the reaction process in order to provide a margin of safety if needed depending on the limitations of the equipment being used. We have found it convenient to operate at pressures of about 50 to about 500 psig. The upper limit for pressure is generally a limitation of the available equipment. The reactor consisted of a stirred autoclave fitted  
10 with a packed column attached to a condenser maintained at about  $0^\circ\text{C}$  to about  $-20^\circ\text{C}$ . Excess pressure ( $\text{HCl}$ ) is vented through a valve at the top of the condenser into a scrubber. At the end of the heating period, the product and remaining  $\text{HF}$  are vented through a valve on the autoclave head, which in turn is connected to an acid scrubber and cold traps to collect the product. Under-fluorinated materials, such as  $\text{CF}_2\text{ClCH}_2\text{CF}_2\text{Cl}$   
15 may be recycled along with  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  in subsequent batch runs. The process may also be conducted in a continuous mode by removing a product stream at a rate equal to the rate at which the reactants are continuously fed into the reactor.

The mole ratio of  $\text{HF}$  to organic should be about 4/1 to about 20/1, preferably about 5/1 to about 9/1. Since over-fluorinated material,  $\text{CF}_3\text{CH}_2\text{CF}_3$ , is generally not  
20 desired, it is more advantageous to allow more under-fluorinated material (which can be recycled) in the crude product. Over-fluorinated product is kept low by smaller  $\text{HF}$ /organic ratios and lower reaction temperatures. In a batch mode, reaction time is also an important parameter to keep low over-fluorination. Under batch mode conditions, the reaction times range from about one to about 25 hours, preferably from about one to  
25 about ten hours, most preferably from about one to about five hours, and can be monitored by the rate of pressure ( $\text{HCl}$ ) increase.



Pentavalent antimony halides are commercially available. Antimony pentachloride ( $\text{SbCl}_5$ ) is most preferred because of its low cost and availability. Some catalyst deactivation is observed with  $\text{SbCl}_5$ , which is attributed generally to the formation of Sb (III) halides. Thus, chlorine is used as a co-feed in continuous liquid phase fluorination reactions to maintain the antimony in the +5 oxidation state. Pentavalent antimony mixed halides of the formula  $\text{SbCl}_n\text{F}_{5-n}$  where n is 1 to 5 tend to be created in situ upon reaction with HF and are also preferred. The fluorination catalysts used in this invention preferably have a purity of at least about 97%. Although the amount of fluorination catalyst used may vary widely, we recommend using from about 5 to about 13 mol%, preferably about 6 to about 12 mol%, most preferably from about 7 to about 11 mol%, relative to  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ .

The difficulty in conducting the fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  so as to obtain chiefly  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  can be appreciated by the fact that with HF alone (no fluorination catalyst) relatively low yields of the desired  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  were obtained, the reaction affording primarily under-fluorinated products. With a liquid fluorination catalyst ( $\text{SbF}_5$ ), a high yield of over-fluorinated product,  $\text{CF}_3\text{CH}_2\text{CF}_3$ , was obtained (see Examples 2 and 3).

For example, using  $\text{SbCl}_5$  as the catalyst at a concentration of 1 mol% (relative to  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ ) and a reaction temperature of  $100^\circ\text{C}$ , the ratio of products was 43.3%  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  and 54.5%  $\text{C}_3\text{H}_2\text{Cl}_2\text{F}_4$  after 50 hours. By increasing the catalyst concentration to 5 mol%, a similar product distribution was achieved in 15 hours at the same temperature. By increasing the concentration of catalyst even further to 8.5 mol%, the product distribution was 51.4%  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  and 44.1%  $\text{C}_3\text{H}_2\text{Cl}_2\text{F}_4$  at a lower reaction temperature of  $79^\circ\text{C}$ . In each of the above cases, the amount of  $\text{CF}_3\text{CH}_2\text{CF}_3$  was below 3%. However, further increasing the catalyst concentration to 16.7 mol% and lowering the temperature to  $56^\circ\text{C}$ , did not prevent the formation of a substantial (8.5%) amount of the over-fluorinated product,  $\text{CF}_3\text{CH}_2\text{CF}_3$ . Thus, mole ratios (relative to organic) of about 13 to 18% resulted in unacceptable amounts of over-fluorinated

product, while concentrations below about 5 mole % are less preferred due to reduced productivity. Good results were obtained at  $\text{SbCl}_3$  concentrations of about 10 mole %.

Vapor phase fluorination reactions also may be used successfully. Reaction temperatures range from about  $100^\circ\text{C}$  to about  $400^\circ\text{C}$ , more preferably from about  $250^\circ\text{C}$  to about  $350^\circ\text{C}$ . Suitable vapor phase catalysts principally include those based on chromium and aluminum salts and oxides (e.g. chrome oxide and aluminum fluoride) which may be modified with varying amounts of other transition metal salts and oxides such as those of manganese, nickel, cobalt, and iron. Thus, acceptable catalyst formulations may include, for example, mixtures of  $\text{Cr}_2\text{O}_3/\text{AlF}_3/\text{CoCl}_2$ ,  $\text{Cr}_2\text{O}_3/\text{NiO}/\text{CoCl}_2$ ,  $\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{Cr}_2\text{O}_3/\text{AlF}_3$ ,  $\text{Cr}_2\text{O}_3/\text{carbon}$ ,  $\text{CoCl}_2/\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{NiCl}_2/\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{CoCl}_2/\text{AlF}_3$  and  $\text{NiCl}_2/\text{AlF}_3$ . It is to be appreciated that the composition of the catalyst may change (e.g. undergo fluorination) during the initial fluorination process which will achieve a steady state composition after some time of operation. Such catalysts are conveniently handled in pelletized form (commonly  $1/8$  " pellets). Chrome (III) oxide, supported or by itself, is the preferred catalyst.

The HF and hexachloropropane (HCC-230f) feeds are adjusted to the desired mole ratio, which preferably ranges from about 3:1 to about 100:1; more preferably from about 4:1 to about 50:1 and most preferably from about 5:1 to about 20:1.

Reaction pressure is not critical and can be superatmospheric, atmospheric or under vacuum. The vacuum pressure can be from about 5 torr to about 760 torr.

During the fluorination reaction, HCC-230f and HF are reacted in a vapor phase with the fluorination catalyst. The reactant vapor is allowed to contact the fluorination catalyst for from about 1 to about 120 seconds, preferably from about 1 to about 50 seconds, more preferably from about 1 to about 30 seconds. For purposes of this invention, "contact time" is the time required for the gaseous reactants to pass through the catalyst bed assuming that the catalyst bed is 100% void.

Before each use, the catalyst is preferably dried, pretreated and activated. It may also be advantageous to periodically regenerate the catalyst after prolonged use while in place in the reactor. Pre-treatment can be done by heating the catalyst to about 250 °C to about 430°C in a stream of nitrogen or other inert gas. The catalyst may then be activated  
5 by treating it with a stream of HF diluted with a large excess of inert gas in order to obtain high catalyst activity. Regeneration of the catalyst may be accomplished by any means known in the art such as, for example, by passing air or air diluted with inert gas over the catalyst at temperatures of from about 100°C to about 400°C, preferably from about 200°C to about 375°C, for from about 8 hours to about 3 days, depending on the size of  
10 the reactor.

In the last step,  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  is reduced to 1,1,1,3,3-pentafluoropropane. The reduction can be conveniently accomplished in a continuous flow system by passing vapors of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ , along with hydrogen, over a reduction catalyst. Certain olefinic by-products of the fluorination step, e.g.,  $\text{CF}_3\text{CH}=\text{CF}_2$ , also will be reduced to provide  
15  $\text{CF}_3\text{CH}_2\text{CHF}_2$ .

Reduction catalysts include nickel, palladium, platinum and rhodium, which are usually supported on inert materials, such as carbon or alumina. These catalysts are available commercially and generally can be obtained having about 0.5 to about 20% by weight of the metal on the support material. More commonly, a loading of about 0.5 to  
20 about 5% weight percent is employed. Examples include 1% palladium on activated carbon granules and 0.5% platinum on 1/8" alumina pellets. The more preferred catalyst is palladium due to its lower cost compared to either platinum or rhodium.

While it is most convenient to operate to atmospheric pressure, this is not required. Both subatmospheric pressures or pressures up to about 100 atmospheres may be used,  
25 the latter especially in batch operations.

In the hydrogenation step it may be preferable to utilize a solvent, such as methanol, ethanol and acetic acid. A base may also be beneficial to neutralize the HCl produced. Any neutralizing agent can be used, e.g., sodium hydroxide, potassium hydroxide, sodium acetate and sodium carbonate.

- 5            Useful temperatures for vapor phase reductions range from about 100°C to about 350°C, a more preferred range is from about 150°C to about 250°C.

            Based on reaction stoichiometry, the required ratio of hydrogen to organic is about 1 mole of hydrogen per mole of organic. From about 1 to about 50 times the stoichiometric ratio may be used. A ratio of about 2 to about 30 times the stoichiometric  
10           amounts can be used with satisfactory results.

            The most desirable conditions for the reduction will vary and will depend, in part, on the activity of the catalyst (which depends on the type of metal used, its concentration on the support material, and the nature of the support material), and the contact or residence time in the reactor. Residence times may be adjusted by changing the reaction  
15           temperature, the catalyst volume, and the flow rates of hydrogen and/or organic material to be reduced. Useful contact times range from about 0.1 sec to about 2 minutes. In the present case, more preferred contact times range from about 10 to about 40 seconds at about 200°C to about 225°C and atmospheric pressure.

            In the reduction of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  at atmospheric pressure and at temperatures of  
20           about 100°C to about 325°C, both  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  and  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  are generally present in the reactor effluent stream. The ratio of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  to  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  increases with increasing reaction temperature. Continuous operation at high temperatures ( $> 250^\circ\text{C}$ ) is not very advantageous, due to potential gradual loss of the original catalyst activity. Consequently, the preferred method to achieve relatively high conversions of  
25            $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  to  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  is to increase the contact time, or equivalency, to recycle

the product stream until the desired conversion is obtained. After separating the desired  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  from  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ , the  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  may be fed into the reactor again.

**Example 1 - Preparation of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$**

A Teflon-lined, magnetically stirred autoclave (575 mL capacity) was charged with  
5 150 mL  $\text{CCl}_4$ , 150 mL  $\text{CH}_3\text{CN}$ , 0.51g  $\text{CuCl}$  and 0.51g  $\text{CuCl}_2$  dihydrate. The autoclave  
was closed and evacuated briefly. Vinylidene chloride (57.7g, 0.595 mol) was added via  
syringe and a rubber septum over a ball valve on the autoclave. The autoclave was then  
pressurized with nitrogen to 20 psig at room temperature. The mixture was heated over  
1.75 h to  $150^\circ\text{C}$  and maintained at  $150^\circ\text{C}$  for 2 h. The stirrer speed was maintained at 350  
10 rpm. After cooling the autoclave and contents to about  $15^\circ\text{C}$ , the contents were removed,  
diluted with 400 mL water, and the organic layer separated. The aqueous layer was  
extracted with 50 mL methylene chloride, and the combined organic layers washed with  
100 mL brine. After drying ( $\text{Na}_2\text{SO}_4$ ), the organic layer was concentrated by rotary  
evaporation to give 140.4 g crude product. Distillation at 2.7 mm Hg gave 114.3g  
15  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ , b.p.  $63\text{--}65^\circ\text{C}$  (77% yield based on vinylidene chloride added). Its purity by  
GC analysis was 99.97%.  $^1\text{H}$  NMR ( $\text{CDCl}_3$ ): singlet at 4.17  $\delta$ .

**Example 2 - Fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with HF alone**

An autoclave was charged with 64 g (0.25 mole)  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  and 81 g (4.05  
mole) HF and heated to  $100^\circ\text{C}$  for 22 hours. The major volatile products, identified by  
20 GC-MS analysis, were  $\text{C}_3\text{H}_2\text{Cl}_2\text{F}_4$ ,  $\text{C}_3\text{H}_2\text{Cl}_3\text{F}_3$ , and  $\text{C}_3\text{H}_2\text{Cl}_4\text{F}_2$  isomers, along with some  
olefinic by-products. Note that no monochloro isomers were produced.

**Example 3 - Fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with HF and  $\text{SbF}_5$**

A magnetically stirred autoclave fitted with a condenser maintained at  $-10^\circ\text{C}$  was  
charged with 7.6 g  $\text{SbF}_5$  (0.035 mole) 64 g (0.255 mole) of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ , and 100 g (5.0  
25 mole) of HF. The contents were then heated to  $125^\circ$  for 18 h. During the heating period,

pressure in excess of 400 psig was periodically vented to an aqueous KOH scrubber which was attached to two cold traps maintained at  $-78^{\circ}\text{C}$ . At the end of the heating period, the remainder of the contents were slowly vented. The cold traps contained 33.4 g of colorless liquid which consisted of 97.9%  $\text{CF}_3\text{CH}_2\text{CF}_3$  and 0.5%  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ .

5 **Example 4 - Liquid phase fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$**

An autoclave was charged with 1 mole  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ , 0.97 mol  $\text{SbCl}_5$  and 7.55 mol HF, and heated for 1 hour at  $52-72^{\circ}\text{C}$ , 0.5 hour at  $72-82^{\circ}\text{C}$  and finally 2 hours at  $80-82^{\circ}\text{C}$ . The operating pressure varied from 100 to 300 psig (periodic venting of HCl). The crude product consisted of 76.7%  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ , 4%  $\text{CF}_3\text{CH}_2\text{CF}_3$  and 14.7%  $\text{C}_3\text{H}_2\text{Cl}_2\text{F}_4$ . The catalyst was then regenerated for the next batch by bubbling chlorine gas into the autoclave and stirring for 2 hours.

**Example 5 - Continuous liquid-phase fluorination process with  $\text{HF/SbCl}_5$**

In a typical liquid phase fluorination process, operating in a continuous mode, about 182 Kg of antimony pentachloride catalyst is charged to a 50 gal reactor. The reactor temperature is raised to  $85^{\circ}\text{C}$ . Reactants are then continuously fed into the reactor at the following rates:  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ , 25.2 Kg/h; HF, 15 Kg/h;  $\text{Cl}_2$ , 0.68 Kg/h. The reactor pressure is maintained at about 150 psig by venting the product stream through a condenser, as was done in Example 3. The product stream consists of HCFC-235fa (1-chloro-1,1,3,3,3-pentafluoropropane), HFC-236fa (1,1,1,3,3,3-hexafluoropropane), 1,1,3,3,3-pentafluoropropene, HF, HCl and other minor amounts of organic by-products. The HCl, HF and residual chlorine are removed from the product stream by passing the effluent stream through a caustic scrubber. The acid-free product stream contains 60% HCFC-235fa, 10% HFC-236fa and 25% 1,1,3,3,3-pentafluoropropene.

**Example 6 - Vapor phase fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$** 

In a typical run, a reactor of 1" diameter MONEL pipe is used. About 132 g (about 1.33 g/cc bulk density) chromium (III) oxide was charged to the reactor. The catalyst was dried and pretreated with HF before use. The reactor is preheated to the  
5 reaction temperature while anhydrous HF is fed into the reactor at atmospheric pressure. The organic feed ( $\text{CCl}_3\text{CH}_2\text{CCl}_3$ ) was started when reactor reached 250°C. The HF and organic feeds were then adjusted to the desired rates. The HF/organic mole ratio is kept at about 7-8 to 1. The effluent product stream was analyzed by using an in-line GC. The product stream is fed to a caustic scrubber and the organic product mixture is collected. It  
10 contains about 50% HCFC-235fa, 20% HFC-236fa, 25% 1,1,3,3,3-pentafluoropropene and other minor amounts of organic by-products.

**Example 7 - Reduction of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  at 200°C**

The reactor used in this Example consisted of an electrically heated glass column containing a catalyst bed comprised of a mixture of 10 cc 1% Pd on activated carbon (4-8  
15 mesh) and 15 cc glass helices. Hydrogen was passed over the catalyst at 140 cc/min and  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  was introduced at a rate of 2.25 g/h. The reaction temperature was 200°C. The material exiting the reactor was collected in a cold trap and consisted of approximately 1/3  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$  and 2/3 unreacted  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  by GC analysis. The single pass yield was about 33%.

**20 Example 8 - Reduction of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  at 225°C**

Example 7 was repeated, except that the reaction temperature was increased to 225°C. The volatile material which collected in the cold trap consisted, by GC analysis, of 51%  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ . The remainder was primarily unreacted  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ . Distillation gave  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ , b.p. 14°C. The recovered  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  was recycled to provide  
25 additional  $\text{CF}_3\text{CH}_2\text{CF}_2\text{H}$ .

**Example 9- Reduction of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  at room temperature**

An autoclave was charged with a solution of 10g KOH in 60 mL methanol, 0.5g 1% Pd on carbon, and 25g (0.15 mol)  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ . Stirring was begun and the autoclave pressurized to 250 psig with hydrogen. After 20 hours, the contents were  
5 cooled to 0°C and excess hydrogen was bled off. The remaining volatile organic material was then transferred to a cold receiver under vacuum. Distillation of the crude material so obtained gave  $\text{CF}_3\text{CH}_2\text{CHF}_2$ . The yield was greater than 80%.

**Example 10 - Reduction of the product stream from the fluorination of  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with  $\text{HF/SbCl}_5$  operating in a continuous mode**

10 About 1 lb. of Pd/alumina catalyst is packed into a 2" x 4' MONEL hydrogenation reactor. The acid-free product stream (about 100 lbs) obtained from Example 6 is fed to the hydrogenation reactor at a rate about 0.1 lb./hour along with a hydrogen feed of about 30 liters/hr. The temperature in the reactor, operated at 100 psi, is about 150°C. The exiting stream is passed through a caustic scrubber to remove HCl.  
15 Subsequently, the stream exiting the scrubber is fed into a 2" diameter distillation column. The distillation is conducted in a batch mode. HFC-245fa is isolated with > 99% purity. The single pass yield is about 72% based on HCFC-235fa. Unreacted HCFC-235fa can be recycled to improve overall yield.



What is Claimed is:

1. A process for the preparation of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  in the liquid phase comprising fluorinating  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with hydrogen fluoride in a mole ratio of hydrogen fluoride to organic of about 4/1 to about 20/1 in the presence of about 5 mol% to about 13  
5 mol% of a pentavalent antimony halide fluorination catalyst of the formula  $\text{SbCl}_n\text{F}_{5-n}$  where n is 1 to 5 wherein the fluorination reaction is conducted at a temperature of about 50°C to about 100°C.
2. The process of claim 1 wherein the fluorination catalyst is  $\text{SbCl}_5$ .
3. The process of claim 1 wherein the fluorination catalyst is present in an amount of  
10 from about 7 mol% to about 11 mol% relative to  $\text{CCl}_3\text{CH}_2\text{CCl}_3$ .
4. The process of claim 1 wherein the reaction is conducted at about 75°C to about 95°C.
5. The process of claim 1 wherein the reaction is conducted in a pressurized reactor at a pressure of about 50 to about 500 psig.
- 15 6. A process for the preparation of  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  comprising contacting  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  with hydrogen fluoride in the vapor phase in the presence of a fluorination catalyst.
7. The process of claim 6 wherein the reaction is conducted at about 100°C to about 400°C.
8. The process of claim 6 wherein the molar ratio of hydrogen fluoride to  $\text{CCl}_3\text{CH}_2\text{CCl}_3$   
20 is about 3:1 to about 100:1.
9. The process of claim 6 wherein the molar ratio of hydrogen fluoride to  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  is about 5:1 to about 20:1.
10. The process of claim 6 wherein the contact time is from about 1 to about 120 seconds.

11. The process of claim 6 wherein the contact time is from about 1 to about 30 seconds.
12. The process of claim 6 wherein the fluorination catalyst is a transition metal salt, a transition metal oxide or a mixture thereof.
13. The process of claim 12 wherein the fluorination catalyst is a chromium oxide, an  
5 aluminum fluoride or a mixture thereof.
14. The process of claim 13 wherein the fluorination catalyst is modified with an oxide or a salt of a transition metal selected from the group of manganese, nickel, cobalt, iron and mixtures thereof.
15. The process of claim 14 wherein the fluorination catalyst is selected from the group  
10 consisting of  $\text{Cr}_2\text{O}_3/\text{AlF}_3/\text{CoCl}_2$ ,  $\text{Cr}_2\text{O}_3/\text{NiO}/\text{CoCl}_2$ ,  $\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{Cr}_2\text{O}_3/\text{AlF}_3$ ,  $\text{Cr}_2\text{O}_3/\text{carbon}$ ,  $\text{CoCl}_2/\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{NiCl}_2/\text{Cr}_2\text{O}_3/\text{Al}_2\text{O}_3$ ,  $\text{CoCl}_2/\text{AlF}_3$  and  $\text{NiCl}_2/\text{AlF}_3$ .
16. The process of claim 6 wherein the fluorination catalyst is chrome (III) oxide.
17. The process of claim 1 or 6 further comprising the step of recycling materials produced other than  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$ .
- 15 18. The process of claim 1 or 6 wherein the reaction is conducted in a continuous mode.
19. The process of claim 1 or 6 wherein the  $\text{CCl}_3\text{CH}_2\text{CCl}_3$  is prepared by reacting  $\text{CCl}_4$  with vinylidene chloride.
20. The process for the preparation of 1,1,1,3,3-pentafluoropropane comprising reacting  
20  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  with hydrogen in the presence of a reduction catalyst wherein the said  $\text{CF}_3\text{CH}_2\text{CF}_2\text{Cl}$  is prepared by the process of claim 1 or 6.

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 99/06868

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C07C17/20 C07C19/10 C07C19/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 522 639 A (SOLVAY) 13 January 1993 (1993-01-13) cited in the application column 2, line 12-55 column 3, line 17-22 example 1B claims 5,6,8	1-5, 17-20
A	EP 0 728 720 A (DAIKIN IND LTD) 28 August 1996 (1996-08-28) the whole document	17-20



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

### \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*3\* document member of the same patent family

Date of the actual completion of the international search

5 July 1999

Date of mailing of the international search report

29.09.99

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Goetz, G

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 99/ 06868

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely: —
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

1 - 5 (completely), 17 - 20 (in part)

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

## INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 99/06868

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

1. Claims: 1-5 (completely), 17-20 (in part)

Process for preparing  $\text{CF}_3\text{-CH}_2\text{-CF}_2\text{Cl}$  in the liquid phase by fluorination of  $\text{CCl}_3\text{-CH}_2\text{-CCl}_3$  with HF in a specific ratio in the presence of a pentavalent antimony catalyst in a specific molar amount at a specified temperature range.

2. Claims: 6-16 (completely), 17-20 (in part)

Process for preparing  $\text{CF}_3\text{-CH}_2\text{-CF}_2\text{Cl}$  by fluorination of  $\text{CCl}_3\text{-CH}_2\text{-CCl}_3$  in the vapor phase in the presence of any fluorination catalyst.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/06868

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0522639 A	13-01-1993	BE 1005096 A	20-04-1993
		CA 2073533 A	11-01-1993
		DE 69202207 D	01-06-1995
		DE 69202207 T	30-11-1995
		ES 2074328 T	01-09-1995
		JP 5201892 A	10-08-1993
-----			
EP 0728720 A	28-08-1996	JP 7138194 A	30-05-1995
		WO 9513256 A	18-05-1995
-----			